

Angel Tablet Charger



Angel Charger is a high-quality, durable, long-lasting product for frequent use. It is safe and user-friendly, manufactured to ISO9001 standards. The charging cabinet is designed to organize and charge tablets with microprocessors controlling the charging system for long lasting battery with surge protection and grounding to ensure safety according to national safety standards.

Device Specifications

Model : T-10 T-12 T-20 T-24 T-30 T-36
T-40 T-48 T-45L T-60L



1. Cabinet can charge tablets in quantities of 10, 12, 20, 24, 30, 36, 40, 45, 48 or 60 depending on the model.
2. Made from 1.6 mm thick steel, coated with durable Power Coating.
3. Clear acrylic front door allows easy viewing of inside contents.
4. Comes with 3 mm. thick stainless steel handle for easy repositioning (T-10 and T-12 excluded).
5. 360-degree rotating wheels with a locking system for easy mobility and secure positioning.
6. Front and rear doors equipped with a key lock for enhanced safety.
7. Ventilation system on both sides with steel grating covering the fans for added safety (T-10 and T-12 models excluded).
8. Steel-lined slots coated with PE plastic to protect tablets from scratches.
9. Side cable storage slots for neat organization and user convenience.
10. Plug-in terminal system for the circuit board allows easier assembly and maintenance.
11. Safe design for educational use suitable for students and teachers.
12. Certified according to industrial safety standards and ISO9001.



Digital timer display for setting charging duration from 10 minutes to 24 hours.



Power cable certified to TIS 11-2553 and power socket with TIS 166-2549 standards.



Tablet slots are made from a 1.6 mm thick steel cabinet and coated with PE plastic to protect tablets from scratches.



Built-in surge protection to prevent damage from power surges and unstable current.



High-strength wheels support heavy loads, rotate 360 degrees, and include brakes to prevent sliding.



Durable stainless steel handle for easy repositioning, with side ventilation and lockable front and rear doors.



www.angeltablet.com

www.angeladvance.com

Angel Advance Tech Co., Ltd.

29 Soi Ladpraowanghin 76 Ladpraowanghin Rd., Ladprao
Bangkok 10230

Line ID : [angeladvance](https://line.me/tv/angeladvance)

E-Mail : sales.angeladvance@gmail.com

Tel : 02-942-2436-7 Fax : 02-942-2418

Angel Tablet Charger



T-45L T-60L

T-40 T-48


T-30 T-36

T-20 T-24

T-10 T-12

Technical Feature

1. Microcontroller-based charging system ensures high precision and stability.
2. The digital timer display allows users to set charging durations between 10 minutes and 24 hours, in 10-minute intervals. The display shows the remaining time during charging and indicates when charging is complete.
3. The automatic cut-off system resumes charging automatically after a power outage and stops charging once the battery is full to prevent overcharging and extend battery life.
4. Solid State Relay with Zero Voltage Crossing prevents power spikes during charging.
5. Charging system is divided into groups of 10–20 tablets to prevent current overload and ensure all tablets are fully charged.
6. Ventilation system automatically activates the fans during charging and for 5 minutes after charging is complete to reduce internal heat.
7. Circuit board with Plastic Coating to protect against chemicals, insects, and moisture.
8. Durable, certified power outlets, each with an indicator light showing charging status, are fused to prevent overcurrent and provide surge protection.
9. The power cable is certified to TIS 11-2553, and the power sockets comply with TIS 166-2549 standards.
10. An optional safety breaker system (ELCB) is available for enhanced protection.

Model	No. of Slots	Slot Width	Cabinet Size (WxHxD)	Supported Tablet Size
T-60L	60	27 mm.	80 x 97 x 60 cm.	
T-45L	45	30 mm.		
T-48	48	27 mm.	52 x 122 x 56 cm.	
T-40	40	30 mm.		
T-36	36	27 mm.	52 x 97 x 56 cm.	
T-30	30	30 mm.		
T-24	24	27 mm.	52 x 80 x 56 cm.	
T-20	20	30 mm.		
T-12	12	27 mm.	52 x 62 x 56 cm.	
T-10	10	30 mm.		